



Epoxy 21 SL

Quantum Coatings is a proud member of the **Quantum Group** of companies.

DESCRIPTION

Epoxy 21-SL is a self-leveling, two part epoxy with zero VOC (100% solids) and excellent physical properties.

Epoxy 21-SL is formulated to provide a balance of flexibility and hardness. **Epoxy 21-SL** can be applied to a wide range of substrates.

PROPERTIES

(of cured product*)

Density	1.2 g/mL
Service Temperature	-40°C to 80°C.
Shore Hardness	80D
Elongation	approx. 25%
Tensile Strength	2500 to 3000 psi
Mix Ratio (Comp A/Comp B)	2:1

STORAGE

Store in a cool and dry place for product integrity. Store in tightly sealed containers to protect from moisture and foreign materials.

PRODUCT SAFETY

For details an MSDS is available from Quantum Coatings.

*Approximate values only. Should not be considered specifications. This data sheet is intended for general information only. Updated November 1, 2001

INSTRUCTIONS

Detailed instructions for use are available from Quantum Coatings.

FEATURES

- Easy to apply.
- Solvent free.
- Resistant to impact over wide temperature range.
- Resistant to cracking under flex conditions.
- Remains flexible at low temperatures.
- Resistant to water and a wide range of chemicals.
- Can be tinted to a wide range of colours.

AVAILABILITY

Epoxy 21-SL is packaged in 5 US Gallon pails.

OTHER

The purchaser of this product must rely on his own judgement in determining suitability for his purpose, and in applying directions as to handling and use. Quantum makes no warranty, expressed or implied, except that if this product proves on inspection to be defective, Quantum will replace it or refund the purchase price. Labour costs and other consequential damages are hereby excluded. No representative or purported agent of Quantum has the authority to change this warranty.